


Thermal Receipt Printer

RETSOL RTP-82UE



USB+LAN Interfaces



- » New sleek shell design
- » Wall mount capable
- » Easy drop-in paper loading
- » Intelligent cutter control system
- » Order comes remind
- » USB + LAN Interfaces

Technical Specification



Model	RTP-82UE
Printing method	Direct thermal
Paper width	58±0.5mm / 79.5±0.5mm
Print width	72mm / 76mm / 80mm / 64mm / 48mm / 52mm
Column capacity	576 dots / line (adjustable by command)
Printing Speed	230 mm/s
Line Spacing	3.75mm (Adjustable by commands)
Interface	USB + LAN
Auto cutter	Partial

Physical Characteristics

Weight	0.97 Kg
Dimensions	D 180 x W 140 x H 134.1mm

Power	
Power adaptor	Input: AC 100-240V / 50~60Hz; Output: DC 24V / 2.5A
Printer input	DC 24V / 2.5A
Cash drawer	DC 24V / 1A

Environmental Requirements

Operational environment	Temperature (0 ~ 45°C) Humidity (10 ~ 80%)
Storage environment	Temperature (-10 ~ 60°C) Humidity (10 ~ 90%)

Reliability

Cutter life	1.5 million cuts
Printer head life	150Km

Software

Emulation	ESC/POS
Driver	Windows / JPOS / OPOS / Linux / Android / Mac
Utility	Windows & Linux test Utility
SDK	IOS / Android / Windows

Warranty

Warranty	One year factory warranty*
----------	----------------------------

* Warranty - Against Manufacturing Defects on the Printer
Specifications are subject to change without notice

